

1500W High Power Laser Diode

BDL-CW1500



Features:

- Good power stability
- Good system reliability
- Easy-to-use control
- Cost effective and maintenance free

Applications:

- Laser welding
- Laser cladding
- Surface treatment
- Laser edge banding

Optical Character	
Power	1500W
Wavelength	976 nm
Output Fiber Core Diameter	400 μ m
Output Cable Length	10 m or customized
Output Cable Connector	QBH
Aiming Beam	Red
Operation Mode	CW or modulation
Polarization	Random
Power Stability (25°C)	$<\pm 1.5\%$ (2h)
Power Adjustment Scope	10%-100%
Max Modulation Frequency	5kHz
Size and Weight	
Physical Size (H×W×D)	80mm*402mm*296mm
Weight	15 kg
Electronic Character	
Power Supply	220 $\pm$ 20 V, AC, PE, 50/60 Hz
Power Consumption	4.5 kW
Control Interface	RS232/AD
Water Cooling Parameters	
Minimum Water Cooling Capacity	3.5 kW
Temperature Settings	25°C (Laser Module), 30°C (QBH)
Cooling Tubes Size	O.D. Φ 12 mm
Cooling Water Flow Rate (Laser)	>15 L/min
Cooling Water Flow Rate (QBH)	1.5~2.0 L/min

1500W High Power Laser Diode

BDL-CW1500

Package Dimensions (mm)

